


Specification for monolithic crystal filter:


MQF 21.4-2400/07

1. General

1.1. Package:



GM17



- | | |
|-----------------------------------|------------------|
| 1.2. Type name: | MQF 21.4-2400/07 |
| 1.3. Number of poles: | 12 |
| 1.4. Operating temperature range: | -40°C to +80°C |
| 1.5. Storage temperature range: | -55°C to +95°C |

2. Electric values

- | | |
|---------------------------------------|----------|
| 2.1. Nominal centre frequency f_0 : | 21.4 MHz |
|---------------------------------------|----------|

2.2. Pass band

- | | |
|---|------------------------------------|
| 2.2.1. Bandwidth between 6 dB - frequencies: | $\geq f_0 \pm 12$ kHz |
| 2.2.2. Ripple: | ≤ 2.0 dB at $f_c \pm 9.6$ kHz |
| 2.2.3. Insertion loss:
(measured on smallest attenuation in pass band) | ≤ 4.0 dB |

2.3. Stop band

- | | |
|--|----------------------------------|
| 2.3.1. $f_0 \pm 20$ kHz | ≥ 60 dB |
| 2.3.2. $f_0 \pm 40$ kHz..... ± 5 MHz | ≥ 85 dB (except spurious) |

- | | |
|--|---------------------|
| 2.4. Terminating impedance (input and output): | 50 Ω // 0 pF |
|--|---------------------|

- | | |
|-------------|---|
| 3. Marking: | manufacturer, date code
MQF 21.4-2400/07 |
|-------------|---|

- | | |
|----------------------------|---|
| 4. Environment conditions: | Corresponding to Vectron standard CF001 |
|----------------------------|---|

Edited by: _____ date: _____ name: _____