

Vectron International

Filter specification

TFS 276A

1/5

Measurement condition

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	750 Ω -6,3 pF	
Output:	560 Ω -6,4 pF	

Characteristics

Remark:

The reference level for the relative attenuation a_{rel} of the TFS 276A is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 1,5 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at 276,0 MHz without any tolerance. The given values for both the relative attenuation a_{rel} and the group delay ripple have to be achieved at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

D a t a		typ. value		tolerance / limit	
Insertion loss (reference level)	a_e	9,0	dB	max.	11,0 dB
Nominal frequency	f_N	-			276,0 MHz
Centre frequency	f_c	276,0	MHz	±	100,0 kHz
Passband	PB	-		f_c ±	1,5 MHz
Pass band ripple		2	dB	max.	3,0 dB
Amplitude ripple within $f_N \pm 0,6$ MHz		0,1	dB	max.	0,5 dB
Relative attenuation	a_{rel}				
f_c ... $f_c \pm 1,5$ MHz		2	dB	max.	3 dB
$f_c - 275,7$ MHz ... $f_c - 25,0$ MHz		55	dB	min.	50 dB
$f_c \pm 3,0$ MHz ... $f_c \pm 4,0$ MHz		14	dB	min.	13 dB
$f_c \pm 4,0$ MHz ... $f_c \pm 25,0$ MHz		39	dB	min.	35 dB
$f_c + 25,0$ MHz ... $f_c + 224,0$ MHz		60	dB	min.	50 dB
Group delay	at f_N @ 25 °C	497	ns	max.	±10 ns
Phase ripple within $f_c \pm 2,25$ MHz	p-p	3,8	°	max.	12 °p-p
Phase ripple within $f_c \pm 3,00$ MHz	p-p	3,8	°	max.	30 °p-p
Triple transit response suppression		45	dB	min.	38 dB
Return loss within PB at 25 °C		20	dB	min.	12 dB
Return loss within PB		-		min.	10 dB
Input power level	**	-		max.	20 dBm
Operable temperature range		-			- 40 °C ... + 105 °C
Operating temperature range	OTR	-			- 40 °C ... + 85 °C
Storage temperature range		-			- 62 °C ... + 105 °C
Frequency inversion temperature		22	°C		-
Temperature coefficient of frequency	TC_f ***	-0,04	ppm/K ²		-

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

**) for short term operation only, cycle time 1:1000; 15 dBm max for continuous operation

***) $\Delta f(\text{Hz}) = TC_f(\text{ppm/K}^2) \times (T - T_0)^2 \times f_{cat}(\text{MHz})$.



Generated:

Checked / Approved:

Vectron International GmbH & Co. KG
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: ft@vectron.com


Vectron International GmbH & Co. KG reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Filter characteristic



Construction and pin connection


(All dimensions in mm)



- 1 Ground
- 2 Ground
- 3 Ground
- 4 Output
- 5 Output RF Return
- 6 Ground
- 7 Ground
- 8 Ground
- 9 Input
- 10 Input RF Return

Date code: Year + week
 X 2009
 A 2010
 B 2011
 ...

50 Ω Test circuit



Vectron International GmbH & Co. KG
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@vectron.com

VECTRON reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics, reliability

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: three times max.;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;
5. ESD ANSI/ESD S20.20-1999, class 1A for HBM


This filter is RoHS compliant (2002/95/EG, 2005/618/EG)

Packing

- Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;
- | | |
|---|-------------|
| max. pieces of filters per reel: | 3000 |
| reel of empty components at start: | min. 300 mm |
| reel of empty components at start including leader: | min. 500 mm |
| trailer: | min. 300 mm |


Tape (all dimensions in mm)

- W : 16,00 ± 0,3
- Po : 4,00 ± 0,1
- Do : 1,50 +0,1/-0
- E : 1,75 ± 0,1
- F : 7,50 ± 0,1
- G(min) : 0,60
- P2 : 2,00 ± 0,1
- P1 : 8,00 ± 0,1
- D1(min) : 1,50
- Ao : 5,50 ± 0,1
- Bo : 7,50 ± 0,1
- Ct : 13,5 ± 0,1



Reel (all dimensions in mm)

- A : 330
- W1 : 16,4 +2/-0
- W2(max) : 22,4
- N(min) : 50
- C : 13,0 +0,5/-0,2



The minimum bending radius is 45 mm.


Vectron International GmbH & Co. KG
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@vectron.com

VECTRON reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile



History

Version	Reason of Changes	Name	Date
1.0	- Generation of development specification	Strehl	20.01.2009
1.1	- terminating impedances added (preliminary values) - add of typical values, filter characteristics and matching configuration - typical value of group delay at fn changed (preliminary value)	Pfeiffer	06.03.2009
1.2	- terminating impedances fixed - typical value and variation of group delay ripple changed	Pfeiffer	28.04.2009
1.3	- group delay variation over temperature deleted - temperature coefficient added	Pfeiffer	26.05.2009